

TYRES

Product group	Tyres	
Item number	13627230	
Valid tyre size	IF 650 / 65 R 34	
LI / SI / PR	161 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM1000HP	





Notes and features

- IF tyre for tractors in the highest performance range (from 250 hp approx.).
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Wide contact area enables optimal soil protection and can thus increase crop yields.
- Operating costs are reduced through very good traction and low rolling resistance.



Technical Informations

Item number	13627230
EAN	8059971015119
Valid tyre size	IF 650 / 65 R 34
LI / SI / PR	161 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	214,00
Recommended rim size	23
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	1720
Stat. radius (SLR) [mm]	750
Rolling circumference [mm].	5105
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.