

TYRES

Product group	Tyres
Item number	13627241
Valid tyre size	IF 710 / 60 R 34
LI / SI / PR	164 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Sonderpostenkategorie	DA



Notes and features

- IF tyre for tractors in the highest performance range (from 250 hp approx.).
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Wide contact area enables optimal soil protection and can thus increase crop yields.
- Operating costs are reduced through very good traction and low rolling resistance.

Technical Informations

Item number	13627241
EAN	4040658090943
Valid tyre size	IF 710 / 60 R 34
LI / SI / PR	164 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	243,00
Recommended rim size	25
Maximum air pressure [bar].	1,60
Section width (mm)	710
Outer diameter of tyre [mm].	1715
Stat. radius (SLR) [mm]	740
Rolling circumference [mm].	5105
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 D	5000	65		1,60	