

TYRES

Product group	Tyres
Item number	13627276
Valid tyre size	IF 710 / 60 R 38
LI / SI / PR	172 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Sonderpostenkategorie	DA



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- IF tyre for tractors in the highest performance range (from 250 hp approx.).
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Wide contact area enables optimal soil protection and can thus increase crop yields.
- Operating costs are reduced through very good traction and low rolling resistance.

Technical Informations

Item number	13627276
EAN	4040658076220
Valid tyre size	IF 710 / 60 R 38
LI / SI / PR	172 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	289,20
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	720
Outer diameter of tyre [mm].	1840
Stat. radius (SLR) [mm]	825
Rolling circumference [mm].	5515
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		2,40	