

TYRES

Product group	Tyres
Item number	13627290
Valid tyre size	IF 710 / 70 R 42
LI / SI / PR	179 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- IF tyre for tractors in the highest performance range (from 250 hp approx.).
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Wide contact area enables optimal soil protection and can thus increase crop yields.
- Operating costs are reduced through very good traction and low rolling resistance.

Technical Informations

Item number	13627290
EAN	8059971015300
Valid tyre size	IF 710 / 70 R 42
LI / SI / PR	179 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	371,00
Recommended rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	735
Outer diameter of tyre [mm].	2060
Stat. radius (SLR) [mm]	920
Rolling circumference [mm].	6190
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		2,40	