

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 13627344 |
| Valid tyre size | VF 480 / 95 R 54 |
| LI / SI / PR | 180 D / 177 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1000PT |



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Its special lugs with double edge ensure very good grip and low slippage.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- The tyre offers very high load capacities, low soil compaction and excellent traction.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 13627344 |
| EAN | 8059971028997 |
| Valid tyre size | VF 480 / 95 R 54 |
| LI / SI / PR | 180 D / 177 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1000PT |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 280,00 |
| Recommended rim size | DW15L |
| Permitted rim size | TW15L |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 480 |
| Outer diameter of tyre [mm]. | 2295 |
| Stat. radius (SLR) [mm] | 1040 |
| Rolling circumference [mm]. | 6865 |
| Tread depth (mm) | 57,0 |
| Tyre capacity 75% [ltr.] | 735 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 180 D | 8000 | 65 | | 2,80 | |
| 177 E | 7300 | 70 | | 2,80 | |