

TYRES

Product group	Tyres	
Item number	13627354	
Valid tyre size	VF 710 / 75 R 42	
LI / SI / PR	184 D / 181 E	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM1000PT	



Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- Its special lugs with double edge ensure very good grip and low slippage.
- The tyre offers very high load capacities, low soil compaction and excellent traction.



Technical Informations

Item number	13627354
EAN	8059971031768
Valid tyre size	VF 710 / 75 R 42
LI / SI / PR	184 D / 181 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	387,00
Recommended rim size	DW25B
Permitted rim size	DW23B
Maximum air pressure [bar].	2,00
Section width (mm)	740
Outer diameter of tyre [mm].	2160
Stat. radius (SLR) [mm]	935
Rolling circumference [mm].	6400
Tread depth (mm)	67,0
Tyre capacity 75% [ltr.]	821
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 D	9000	65		2,00	
181 E	8250	70		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.