

TYRES

Product group	Tyres
Item number	13627360
Valid tyre size	VF 900 / 60 R 42
LI / SI / PR	189 D / 186 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Its special lugs with double edge ensure very good grip and low slippage.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- The tyre offers very high load capacities, low soil compaction and excellent traction.

Technical Informations

Item number	13627360
EAN	8059971028379
Valid tyre size	VF 900 / 60 R 42
LI / SI / PR	189 D / 186 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	451,49
Recommended rim size	DW30B
Permitted rim size	DW28B, TW30B
Maximum air pressure [bar].	2,00
Section width (mm)	883
Outer diameter of tyre [mm].	2150
Stat. radius (SLR) [mm]	911
Rolling circumference [mm].	6445
Tread depth (mm)	64,0
Tyre capacity 75% [ltr.]	996
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 D	10300	65		2,00	
186 E	9500	70		2,00	