

TYRES

Product group	Tyres
Item number	13627366
Valid tyre size	VF 380 / 85 R 46
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Its special lugs with double edge ensure very good grip and low slippage.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- The tyre offers very high load capacities, low soil compaction and excellent traction.

Technical Informations

Item number	13627366
EAN	8059971029208
Valid tyre size	VF 380 / 85 R 46
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000PT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	150,00
Recommended rim size	DW12
Permitted rim size	W12, W13, DW13
Maximum air pressure [bar].	2,80
Section width (mm)	360
Outer diameter of tyre [mm].	1825
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5490
Tread depth (mm)	48,0
Tyre capacity 75% [ltr.]	245
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4750	65		2,80	
159 E	4375	70		2,80	