Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	14826080	
Valid tyre size	650 / 85 R 38	
LI / SI / PR	173 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION XXL	



Notes and features

- The Traxion XXL was developed for tractors with an engine performance above 160 hp.
- Its special tread pattern and flexible casing provide a large contact area and thus even ground pressure distribution.
- The large tyre volume enables a high load capacity at low inflation pressure.
- In field applications, the tyre offers excellent traction.
- In transport journeys, it distinguishes itself through high ride comfort and safety at speeds up to 70 km/h.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	14826080
EAN	8714692206221
Valid tyre size	650 / 85 R 38
LI / SI / PR	173 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION XXL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	323,02
Recommended rim size	DW23B
Permitted rim size	DDW21B, DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	710
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	940
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6195
Tread depth (mm)	55,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	850
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.