

TYRES

Product group	Tyres
Item number	14826550
Valid tyre size	480 / 80 R 50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

Item number	14826550
EAN	8714692327216
Valid tyre size	480 / 80 R 50
Alternative size 1	18.4R50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	209,67
Recommended rim size	DW16L
Permitted rim size	W14L, DW14L, W15L, DW15L, W16L
Maximum air pressure [bar].	2,40
Section width (mm)	500
Outer diameter of tyre [mm].	2045
Stat. radius (SLR) [mm]	950
Rolling circumference [mm].	6225
Tread depth (mm)	49,0
Tyre capacity 75% [ltr.]	550
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		2,40	
159 B	4375	50		2,40	