

TYRES

Product group	Tyres	
Item number	14875320	
Valid tyre size	340 / 80 R 20	
LI / SI / PR	144 A8 / 144 B	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	ENDURION	





Notes and features

- The Vredestein Endurion is an MPT radial tyre for telescopic loaders and similar vehicles.
- Wide lugs arranged at a 45° angle to each other and the high tread pattern percentage ensure a long service life.
- The optimum rubber compound and the particularly sturdy casing increase the service life and guarantee maximum yields.



Technical Informations

Item number	14875320
EAN	8714692336584
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	60,00
Recommended rim size	11
Permitted rim size	W10, W11, 11SDC, 12, 12SC
Maximum air pressure [bar].	4,00
Section width (mm)	355
Outer diameter of tyre [mm].	1055
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3180
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	96
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
144 B	2800	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.