

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 14875350 |
| Valid tyre size | 480 / 80 R 26 |
| LI / SI / PR | 160 A8 / 160 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | ENDURION |



Notes and features

- The Vredestein Endurion is an MPT radial tyre for telescopic loaders and similar vehicles.
- Wide lugs arranged at a 45° angle to each other and the high tread pattern percentage ensure a long service life.
- The optimum rubber compound and the particularly sturdy casing increase the service life and guarantee maximum yields.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 14875350 |
| EAN | 8714692310041 |
| Valid tyre size | 480 / 80 R 26 |
| LI / SI / PR | 160 A8 / 160 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | ENDURION |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 128,00 |
| Recommended rim size | DW15L |
| Permitted rim size | DW16L |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 495 |
| Outer diameter of tyre [mm]. | 1440 |
| Stat. radius (SLR) [mm] | 645 |
| Rolling circumference [mm]. | 4320 |
| Tread depth (mm) | 30,0 |
| Tyre capacity 75% [ltr.] | 283 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 A8 | 4500 | 40 | | 3,20 | |
| 160 B | 4500 | 50 | | 3,20 | |