

TYRES

Product group	Tyres
Item number	14875360
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION



Notes and features

- The Vredestein Endurion is an MPT radial tyre for telescopic loaders and similar vehicles.
- Wide lugs arranged at a 45° angle to each other and the high tread pattern percentage ensure a long service life.
- The optimum rubber compound and the particularly sturdy casing increase the service life and guarantee maximum yields.

Technical Informations

Item number	14875360
EAN	8714692310065
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	115,00
Recommended rim size	DW14L
Permitted rim size	DW13L, DW15L
Maximum air pressure [bar].	3,20
Section width (mm)	455
Outer diameter of tyre [mm].	1420
Stat. radius (SLR) [mm]	640
Rolling circumference [mm].	4290
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	238
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,20	
156 B	4000	50		3,20	