

TYRES

Product group	Tyres
Item number	15222559
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360



Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.

Technical Informations

Item number	15222559
EAN	7291050065580
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	176,90
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	600
Outer diameter of tyre [mm].	1480
Stat. radius (SLR) [mm]	684
Rolling circumference [mm].	4481
Tread depth (mm)	48,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	404.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		2,40	