

TYRES

Product group	Tyres
Item number	15225160
Valid tyre size	710 / 60 R 30
LI / SI / PR	165 A8 / 162 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL





Notes and features

- Super volume tyre for high-performance tractors from approx. 200 hp and harvesters.
- Designed for versatile applications.
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against punctures and large contact area.
- Innovative rubber compound for a longer service life and flexible sidewalls (for air pressure adjustment).



Technical Informations

Item number	15225160
EAN	7291050065962
Valid tyre size	710 / 60 R 30
LI / SI / PR	165 A8 / 162 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 378 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	195,00
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	705
Outer diameter of tyre [mm].	1616
Stat. radius (SLR) [mm]	723
Rolling circumference [mm].	4858
Tread depth (mm)	56,7
Number of lugs	19x2
Tyre capacity 75% [ltr.]	367
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		2,40	
162 D	4750	65		2,40	