

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 15225257 |
| Valid tyre size | IF 580 / 85 R 42 CFO |
| LI / SI / PR | 178 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 372 |



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

Technical Informations

| | |
|--------------------------------------|----------------------|
| Item number | 15225257 |
| EAN | 7291050066471 |
| Valid tyre size | IF 580 / 85 R 42 CFO |
| LI / SI / PR | 178 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 372 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 273,00 |
| Recommended rim size | DW20B |
| Permitted rim size | DW18B |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 598 |
| Outer diameter of tyre [mm]. | 2037 |
| Stat. radius (SLR) [mm] | 924 |
| Speed Radius Index (SRI) | 975 |
| Rolling circumference [mm]. | 6047 |
| Contact area [cm²] | 3630 |
| Tread depth (mm) | 56,5 |
| Number of lugs | 22x2 |
| Tyre capacity 75% [ltr.] | 720 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 178 D | 7500 | 65 | | 2,80 | |