

TYRES

Product group	Tyres
Item number	15226100
Valid tyre size	230 / 95 R 32
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226100
EAN	8903635015093
Valid tyre size	230 / 95 R 32
Alternative size 1	9.5R32
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,80
Recommended rim size	8
Permitted rim size	7
Maximum air pressure [bar].	3,60
Section width (mm)	228
Outer diameter of tyre [mm].	1251
Stat. radius (SLR) [mm]	582
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3821
Tread depth (mm)	34,5
Number of lugs	23x2
Lug width (mm)	25
Tyre capacity 75% [ltr.]	68
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		3,60	
128 D	1800	65		3,60	