

TYRES

Product group	Tyres	
Item number	15226130	
Valid tyre size	320 / 85 R 34	
LI / SI / PR	141 A8	
TL/TT	TL	
Brand	Alliance	
Tread pattern	350	





Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	15226130
EAN	8903635021339
Valid tyre size	320 / 85 R 34
Alternative size 1	12.4R34
LI / SI / PR	141 A8
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	72,00
Recommended rim size	W11
Permitted rim size	W10
Maximum air pressure [bar].	3,60
Section width (mm)	329
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	652
Rolling circumference [mm].	4239
Tread depth (mm)	43,5
Number of lugs	24x2
Tyre capacity 75% [ltr.]	138
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		3,60	