

TYRES

Product group	Tyres
Item number	15226733
Valid tyre size	540 / 65 R 24
LI / SI / PR	146 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365



Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.

Technical Informations

Item number	15226733
EAN	8903635014416
Valid tyre size	540 / 65 R 24
LI / SI / PR	146 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	114,90
Recommended rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	550
Outer diameter of tyre [mm].	1315
Stat. radius (SLR) [mm]	577
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3832
Tread depth (mm)	48,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	256
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 D	3000	65		2,40	