

TYRES

Product group	Tyres
Item number	15226761
Valid tyre size	900 / 60 R 32
LI / SI / PR	194 A8 / 191 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15226761
EAN	8903635021841
Valid tyre size	900 / 60 R 32
Alternative size 1	35.5LR32
LI / SI / PR	194 A8 / 191 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	388,00
Recommended rim size	27
Maximum air pressure [bar].	4,40
Section width (mm)	869
Outer diameter of tyre [mm].	1894
Stat. radius (SLR) [mm]	850.00
Rolling circumference [mm].	5645
Tread depth (mm)	56,8
Number of lugs	19x2
Tyre capacity 75% [ltr.]	1056
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
194 A8	11800	40		4,40	
191 D	10900	65		4,40	