

## TYRES

Product group	Tyres
Item number	15226766
Valid tyre size	1050 / 50 R 32
LI / SI / PR	185 A8 / 182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



## Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

**Technical Informations**

<b>Item number</b>	15226766
<b>EAN</b>	7291050063890
<b>Valid tyre size</b>	1050 / 50 R 32
<b>LI / SI / PR</b>	185 A8 / 182 D
<b>TL/TT</b>	TL
<b>Brand</b>	Alliance
<b>Tread pattern</b>	Multistar 376
<b>Carcass properties</b>	Steel Belted
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	387,97
<b>Recommended rim size</b>	36
<b>Maximum air pressure [bar].</b>	3,20
<b>Section width (mm)</b>	1050
<b>Outer diameter of tyre [mm].</b>	1870
<b>Stat. radius (SLR) [mm]</b>	833
<b>Rolling circumference [mm].</b>	5656
<b>Tread depth (mm)</b>	41,0
<b>Number of lugs</b>	20x2
<b>Tyre capacity 75% [ltr.]</b>	1274
<b>Guarantee period</b>	10 years
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 A8	9250	40		3,20	
182 D	8500	65		3,20	