

TYRES

Product group	Tyres
Item number	15226779
Valid tyre size	900 / 60 R 32
LI / SI / PR	185 A8 / 182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375



 **ALLIANCE**

Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	15226779
EAN	7291050058117
Valid tyre size	900 / 60 R 32
LI / SI / PR	185 A8 / 182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	450,66
Recommended rim size	27
Permitted rim size	28, 30
Maximum air pressure [bar].	3,20
Section width (mm)	910
Outer diameter of tyre [mm].	1905
Stat. radius (SLR) [mm]	844
Rolling circumference [mm].	5700
Tyre capacity 75% [ltr.]	1074.75
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 A8	9250	40		3,20	
182 D	8500	65		3,20	