

TYRES

Product group	Tyres
Item number	15226788
Valid tyre size	600 / 65 R 38
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365



Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.

Technical Informations

Item number	15226788
EAN	8903635017417
Valid tyre size	600 / 65 R 38
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	181,16
Recommended rim size	DW20B
Permitted rim size	DW18
Maximum air pressure [bar].	2,40
Section width (mm)	596
Outer diameter of tyre [mm].	1745
Stat. radius (SLR) [mm]	782.00
Rolling circumference [mm].	5284
Tread depth (mm)	49,0
Lug width (mm)	46-49
Tyre capacity 75% [litr.]	478
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	