

TYRES

Product group	Tyres
Item number	15227070
Valid tyre size	14.9 R 26
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

Item number	15227070
EAN	7291050017602
Valid tyre size	14.9 R 26
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	75,44
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	1,60
Section width (mm)	378
Outer diameter of tyre [mm].	1300
Stat. radius (SLR) [mm]	592
Rolling circumference [mm].	3857
Tread depth (mm)	43,0
Number of lugs	20x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	191.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
124 B	1600	50		1,60	