

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 15227328 |
| Valid tyre size | IF 380 / 95 R 38 |
| LI / SI / PR | 154 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 354 |



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 15227328 |
| EAN | 7291050065443 |
| Valid tyre size | IF 380 / 95 R 38 |
| LI / SI / PR | 154 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 354 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 128,86 |
| Recommended rim size | 13 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 391 |
| Outer diameter of tyre [mm]. | 1682 |
| Stat. radius (SLR) [mm] | 767 |
| Rolling circumference [mm]. | 5018 |
| Tread depth (mm) | 48,0 |
| Number of lugs | 30x2 |
| Tyre capacity 75% [ltr.] | 270 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 D | 3750 | 65 | | 2,40 | |