

TYRES

Product group	Tyres
Item number	15227596
Valid tyre size	380 / 85 R 26
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	15227596
EAN	8903635027447
Valid tyre size	380 / 85 R 26
Alternative size 1	14.9R26
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	78,50
Recommended rim size	W12
Permitted rim size	W11
Maximum air pressure [bar].	1,60
Section width (mm)	380
Outer diameter of tyre [mm].	1290
Stat. radius (SLR) [mm]	594
Rolling circumference [mm].	3800
Tread depth (mm)	45,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	162.51
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
127 B	1750	50		1,60	