Bohnenkamp Moving Professionals

14.03.2025

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 15227678 |
| Valid tyre size | 320 / 85 R 34 |
| LI / SI / PR | 133 A8 / 133 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO II |



≈Alliance

Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15227678 |
|------------------------------|----------------|
| EAN | 8903635017349 |
| Valid tyre size | 320 / 85 R 34 |
| LI / SI / PR | 133 A8 / 133 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO II |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 72,80 |
| Recommended rim size | 11 |
| Permitted rim size | W10 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 325 |
| Outer diameter of tyre [mm]. | 1407 |
| Stat. radius (SLR) [mm] | 650 |
| Rolling circumference [mm]. | 4210 |
| Tread depth (mm) | 41,1 |
| Number of lugs | 26x2 |
| Tyre capacity 75% [ltr.] | 146 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 133 A8 | 2060 | 40 | | 2,40 | |
| 133 B | 2060 | 50 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.