

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 15228152 | |
| Valid tyre size | 480 / 70 R 34 | |
| LI / SI / PR | 155 D | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | Agri Star II | |





Notes and features

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.



Technical Informations

| Item number | 15228152 |
|------------------------------|---------------|
| EAN | 8903635028451 |
| Valid tyre size | 480 / 70 R 34 |
| LI / SI / PR | 155 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agri Star II |
| Carcass properties | Stubble Guard |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 146,60 |
| Recommended rim size | W15L |
| Permitted rim size | W14L, W16L |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 482 |
| Outer diameter of tyre [mm]. | 1580 |
| Stat. radius (SLR) [mm] | 731.00 |
| Rolling circumference [mm]. | 4821 |
| Tread depth (mm) | 51,0 |
| Number of lugs | 21x2 |
| Tyre capacity 75% [ltr.] | 331.05 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 155 D | 3875 | 65 | | 3,20 | |