Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15228727
Valid tyre size	380 / 80 R 38
LI / SI / PR	152 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agri Star II



≈Alliance

Notes and features

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15228727 EAN 8903635028857 Valid tyre size 380 / 80 R 38 LI / SI / PR 152 D TL/TT TL Brand Alliance	
Valid tyre size 380 / 80 R 38 LI / SI / PR 152 D TL/TT TL	
LI / SI / PR 152 D TL/TT TL	
TL/TT TL	
Brand Alliance	
Tread pattern Agri Star II	
Carcass properties Stubble Guard	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 106	
Nettogewicht [kg] (gültig) 116,50	
Recommended rim size W12	
Permitted rim size W11, W13	
Maximum air pressure [bar]. 4,00	
Section width (mm) 385	
Outer diameter of tyre [mm]. 1575	
Stat. radius (SLR) [mm] 736	
Speed Radius Index (SRI) 775	
Rolling circumference [mm]. 4827	
Tread depth (mm)46,0	
Number of lugs 23x2	
Tyre capacity 75% [ltr.] 225.98	
Guarantee period 7 years	
E-Ready No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.