

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 15228741      |
| Valid tyre size | 460 / 85 R 38 |
| LI / SI / PR    | 149 D         |
| TL/TT           | TL            |
| Brand           | Alliance      |
| Tread pattern   | Agri Star II  |



## Notes and features

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

**Technical Informations**

|                                     |               |
|-------------------------------------|---------------|
| <b>Item number</b>                  | 15228741      |
| <b>EAN</b>                          | 8903635028536 |
| <b>Valid tyre size</b>              | 460 / 85 R 38 |
| <b>LI / SI / PR</b>                 | 149 D         |
| <b>TL/TT</b>                        | TL            |
| <b>Brand</b>                        | Alliance      |
| <b>Tread pattern</b>                | Agri Star II  |
| <b>Carcass properties</b>           | Stubble Guard |
| <b>Antistatic</b>                   | No            |
| <b>Tyre colour</b>                  | Black         |
| <b>ECE regulation number</b>        | ECE 106       |
| <b>Nettogewicht [kg] (gültig)</b>   | 149,20        |
| <b>Recommended rim size</b>         | W16L          |
| <b>Permitted rim size</b>           | W14L, W15L    |
| <b>Maximum air pressure [bar].</b>  | 1,60          |
| <b>Section width (mm)</b>           | 480           |
| <b>Outer diameter of tyre [mm].</b> | 1747          |
| <b>Stat. radius (SLR) [mm]</b>      | 797.00        |
| <b>Rolling circumference [mm].</b>  | 5194          |
| <b>Tread depth (mm)</b>             | 53,0          |
| <b>Number of lugs</b>               | 22x2          |
| <b>Tyre capacity 75% [ltr.]</b>     | 408.68        |
| <b>Guarantee period</b>             | 7 years       |
| <b>E-Ready</b>                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 149 D | 3250               | 65           |               | 1,60                     |              |