

TYRES

Product group	Tyres
Item number	15235255
Valid tyre size	500 / 85 R 30
LI / SI / PR	170 A8 / 176 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570



Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.

Technical Informations

Item number	15235255
EAN	7291050061032
Valid tyre size	500 / 85 R 30
LI / SI / PR	170 A8 / 176 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	154,57
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,80
Section width (mm)	505
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	698
Rolling circumference [mm].	4802
Tread depth (mm)	39,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40	Drive Wheel	2,80	
176 A8	7100	40	Free Rolling	2,80	