

## TYRES

Product group	Tyres
Item number	15284860
Valid tyre size	365 / 70 R 18
LI / SI / PR	146 A2 / 135 B
TL/TT	TL
Brand	Alliance
Tread pattern	608



## Notes and features

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines.
- High lugs in the shoulder area for traction on loose surfaces.
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces.
- Optimised rolling resistance allows fuel savings.

## Technical Informations

Item number	15284860
EAN	7291050062145
Valid tyre size	365 / 70 R 18
LI / SI / PR	146 A2 / 135 B
TL/TT	TL
Brand	Alliance
Tread pattern	608
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	44,00
Recommended rim size	11
Permitted rim size	13
Maximum air pressure [bar].	3,75
Section width (mm)	360
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	444
Rolling circumference [mm].	2936
Tread depth (mm)	18,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	108
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A2	3000	10		3,75	
135 B	2180	50		3,75	