

TYRES

Product group	Tyres
Item number	15285410
Valid tyre size	340 / 80 R 18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

Technical Informations

Item number	15285410
EAN	8903635029397
Valid tyre size	340 / 80 R 18
Alternative size 1	12.5/80R18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,10
Recommended rim size	11
Permitted rim size	W11, W10, 12SDC, 11SDC, 12
Maximum air pressure [bar].	4,00
Section width (mm)	345
Outer diameter of tyre [mm].	1001
Stat. radius (SLR) [mm]	454
Rolling circumference [mm].	2975
Tread depth (mm)	29,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		4,00	
143 B	2725	50		4,00	