

## TYRES

Product group	Tyres
Item number	15285435
Valid tyre size	440 / 80 R 24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



## Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

## Technical Informations

Item number	15285435
EAN	8903635029588
Valid tyre size	440 / 80 R 24
Alternative size 1	16.9R24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	103,00
Recommended rim size	DW14L
Permitted rim size	DW15L, 14, TW14L
Maximum air pressure [bar].	4,00
Section width (mm)	441
Outer diameter of tyre [mm].	1314
Stat. radius (SLR) [mm]	592
Rolling circumference [mm].	3936
Tread depth (mm)	33,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		4,00	
161 B	4625	50		4,00	