

TYRES

Product group	Tyres
Item number	15710565
Valid tyre size	400 / 50 - 15
LI / SI / PR	109 A8 / 121 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15710565
EAN	8903094060092
Valid tyre size	400 / 50 - 15
LI / SI / PR	109 A8 / 121 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	27,50
Recommended rim size	13LB
Permitted rim size	13
Maximum air pressure [bar].	3,00
Section width (mm)	395
Outer diameter of tyre [mm].	790
Stat. radius (SLR) [mm]	369
Rolling circumference [mm].	2387
Tread depth (mm)	19,5
Number of lugs	14x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40	Drive Wheel	3,00	LLV
121 A8	1450	40	Free Rolling	3,00	LLV