

## **TYRES**

Product group	Tyres	
Item number	15711305	
Valid tyre size	7.00 - 12	
LI / SI / PR	83 A8 / 95 A8, 6 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 504	





## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting



## **Technical Informations**

Item number	15711305
EAN	8903094019274
Valid tyre size	7.00 - 12
LI / SI / PR	83 A8 / 95 A8, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	12,17
Recommended rim size	4.5
Permitted rim size	4.5J, 4.25J, 4J
Maximum air pressure [bar].	3,40
Section width (mm)	187
Outer diameter of tyre [mm].	683
Stat. radius (SLR) [mm]	300
Rolling circumference [mm].	2001
Tread depth (mm)	19,0
Number of lugs	22x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
83 A8	487	40	Drive Wheel	3,40	LLV
95 A8	690	40	Free Rolling	3,40	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.