

TYRES

Product group	Tyres
Item number	15711730
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	123 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
 - Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711730
EAN	8903094009022
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	123 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	16,54
Recommended rim size	9.00
Maximum air pressure [bar].	3,90
Section width (mm)	274
Outer diameter of tyre [mm].	760
Stat. radius (SLR) [mm]	351
Rolling circumference [mm].	2213
Tread depth (mm)	10,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A8	1550	40		3,90	