

TYRES

Product group	Tyres
Item number	15711810
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	133 A8 / 145 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 882



Notes and features

- Bias flotation tyre with traction tread pattern, developed for use on roads and in fields in the most diverse operational and weather conditions.
- Suited to implement applications in the agricultural sector as well as industrial purposes.
- Traction tread pattern for optimal self-cleaning when towed, as well as excellent traction on drive wheels.

Technical Informations

Item number	15711810
EAN	8903094019861
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	133 A8 / 145 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 882
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	37,79
Recommended rim size	13.00
Maximum air pressure [bar].	3,60
Section width (mm)	400
Outer diameter of tyre [mm].	875
Stat. radius (SLR) [mm]	378
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2605
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40	Drive Wheel	3,60	LLV
145 A8	2900	40	Free Rolling	3,60	LLV