

## **TYRES**

Product group	Tyres
Item number	15712440
Valid tyre size	215 / 75 - 17.5
LI / SI / PR	142 A8, 16 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	Rib Master



## Notes and features

• Fine, soil-protecting tread pattern.

• Minimal rolling resistance.



## **Technical Informations**

Item number	15712440
EAN	8903094010905
Valid tyre size	215 / 75 - 17.5
LI / SI / PR	142 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	20,38
Recommended rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	220
Outer diameter of tyre [mm].	775
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2310
Tread depth (mm)	11,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		9,00	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.