

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15715139 |
| Valid tyre size | 560 / 60 R 22.5 |
| LI / SI / PR | 172 A8 / 161 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Ultra |



Notes and features

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15715139 |
| EAN | 8903094052509 |
| Valid tyre size | 560 / 60 R 22.5 |
| Alternative size 1 | 550/60R22.5 |
| LI / SI / PR | 172 A8 / 161 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 630 Ultra |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 112,50 |
| Recommended rim size | AG16.00 |
| Permitted rim size | 16.00, 17.00, AG20.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 543 |
| Outer diameter of tyre [mm]. | 1244 |
| Stat. radius (SLR) [mm] | 535 |
| Speed Radius Index (SRI) | 600 |
| Rolling circumference [mm]. | 3760 |
| Tread depth (mm) | 28,5 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 374 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 172 A8 | 6300 | 40 | | 4,00 | |
| 161 D | 4625 | 65 | | 4,00 | |