

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15715168 |
| Valid tyre size | 710 / 40 R 22.5 |
| LI / SI / PR | 161 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 635 |



Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions as well as fast self-cleaning

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15715168 |
| EAN | 8903094053285 |
| Valid tyre size | 710 / 40 R 22.5 |
| LI / SI / PR | 161 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | FL 635 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 124,30 |
| Recommended rim size | AG24.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 727 |
| Outer diameter of tyre [mm]. | 1140 |
| Stat. radius (SLR) [mm] | 510 |
| Speed Radius Index (SRI) | 550 |
| Rolling circumference [mm]. | 3467 |
| Tread depth (mm) | 24,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 161 D | 4625 | 65 | | 4,00 | |