

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 15715234 |
| Valid tyre size | 600 / 60 R 30.5 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Ridemax FL 693 M |



Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 15715234 |
| EAN | 8903094064335 |
| Valid tyre size | 600 / 60 R 30.5 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Ridemax FL 693 M |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 169,60 |
| Recommended rim size | AG20.00 |
| Permitted rim size | AG18.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 605 |
| Outer diameter of tyre [mm]. | 1495 |
| Stat. radius (SLR) [mm] | 681 |
| Speed Radius Index (SRI) | 725 |
| Rolling circumference [mm]. | 4495 |
| Tread depth (mm) | 23,5 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 D | 5800 | 65 | | 4,00 | |