

TYRES

Product group	Tyres	
Item number	15717160	
Valid tyre size	31 x 15.50 R 15	
LI / SI / PR	122 B	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 511	





Notes and features

- The BKT AS 511 is an implement radial tyre for use on grasslands
- Its tractor tread provides very good self-cleaning properties and traction even on sloping terrains
- Its strong, low-wear rubber compound guarantees a long service life



Technical Informations

	45747400
Item number	15717160
EAN	8903094059782
Valid tyre size	31 x 15.50 R 15
LI / SI / PR	122 B
TL/TT	TL
Brand	BKT
Tread pattern	AS 511
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,26
Recommended rim size	13LB
Permitted rim size	13.00
Maximum air pressure [bar].	2,80
Section width (mm)	388
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	353
Speed Radius Index (SRI)	380
Rolling circumference [mm].	2387
Tread depth (mm)	18,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 B	1500	50		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.