

TYRES

Product group	Tyres
Item number	15717240
Valid tyre size	520 / 50 R 17
LI / SI / PR	151 D / 148 E
TL/TT	TL
Brand	BKT
Tread pattern	FL 637



Notes and features

- The BKT FL637 is a radial flotation tyre for manure spreaders, agricultural trailers and tankers
- Its steel belts provide high loading capacities and long durability
- In the field, the tyre distinguishes itself with very good flotation characteristics, low rolling resistance and good self-cleaning properties
- The directional tread pattern provides excellent traction in field operations
- On the road, the tyre impresses with its good driving characteristics at speeds up to 65 km/h

Technical Informations

Item number	15717240
EAN	8903094054909
Valid tyre size	520 / 50 R 17
LI / SI / PR	151 D / 148 E
TL/TT	TL
Brand	BKT
Tread pattern	FL 637
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	60,25
Recommended rim size	16.00
Maximum air pressure [bar].	5,00
Section width (mm)	516
Outer diameter of tyre [mm].	952
Stat. radius (SLR) [mm]	414
Speed Radius Index (SRI)	450
Rolling circumference [mm].	2930
Tread depth (mm)	15,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		5,00	
148 E	3150	70		5,00	