

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15726035       |
| Valid tyre size | 210 / 95 R 18  |
| LI / SI / PR    | 108 A8 / 108 B |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax RT 855 |



## Notes and features

- Standard tyre of the 85 series for tractors in the mediumpower range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.

- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



## **Technical Informations**

| Item number                  | 15726035       |
|------------------------------|----------------|
| EAN                          | 8903094028672  |
| Valid tyre size              | 210 / 95 R 18  |
| Alternative size 1           | 7.50R18        |
| LI / SI / PR                 | 108 A8 / 108 B |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Agrimax RT 855 |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 23,69          |
| Recommended rim size         | W7             |
| Permitted rim size           | W6             |
| Maximum air pressure [bar].  | 2,40           |
| Section width (mm)           | 214            |
| Outer diameter of tyre [mm]. | 855            |
| Stat. radius (SLR) [mm]      | 385            |
| Speed Radius Index (SRI)     | 410            |
| Rolling circumference [mm].  | 2565           |
| Tread depth (mm)             | 27,0           |
| Number of lugs               | 21x2           |
| Tyre capacity 75% [ltr.]     | 37.64          |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 108 A8 | 1000               | 40           |               | 2,40                        |              |
| 108 B  | 1000               | 50           |               | 2,40                        |              |