

TYRES

Product group	Tyres
Item number	15726160
Valid tyre size	280 / 85 R 28
LI / SI / PR	118 A8 / 118 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726160
EAN	8903094021543
Valid tyre size	280 / 85 R 28
Alternative size 1	11.2R28
LI / SI / PR	118 A8 / 118 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	49,00
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	292
Outer diameter of tyre [mm].	1187
Stat. radius (SLR) [mm]	545
Rolling circumference [mm].	3558
Tread depth (mm)	41,0
Number of lugs	21x2
Lug width (mm)	29
Tyre capacity 75% [ltr.]	93.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A8	1320	40		1,60	
118 B	1320	50		1,60	