

TYRES

Product group	Tyres
Item number	15726290
Valid tyre size	320 / 85 R 34
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726290
EAN	8903094040414
Valid tyre size	320 / 85 R 34
Alternative size 1	12.4R34
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,00
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	3,60
Section width (mm)	329
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	645
Rolling circumference [mm].	4280
Tread depth (mm)	42,0
Tyre capacity 75% [ltr.]	149
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		3,60	
141 B	2575	50		3,60	