

TYRES

Product group	Tyres
Item number	15726310
Valid tyre size	460 / 85 R 34
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726310
EAN	8903094021772
Valid tyre size	460 / 85 R 34
Alternative size 1	18.4R34
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	134,71
Recommended rim size	16
Permitted rim size	14, 15
Maximum air pressure [bar].	1,60
Section width (mm)	475
Outer diameter of tyre [mm].	1646
Stat. radius (SLR) [mm]	721
Rolling circumference [mm].	4865
Tread depth (mm)	52,0
Lug width (mm)	40
Tyre capacity 75% [ltr.]	353.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		1,60	
147 B	3075	50		1,60	