

TYRES

Product group	Tyres	
Item number	15726415	
Valid tyre size	650 / 85 R 38	
LI / SI / PR	176 A8 / 173 D	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax Fortis	



Notes and features

- Super wide tyres for high performance tractors from about 200 hn
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.



Technical Informations

Item number	15726415
EAN	8903094029730
Valid tyre size	650 / 85 R 38
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	350,00
Recommended rim size	DW23B
Permitted rim size	DW21B, DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	675
Outer diameter of tyre [mm].	2071
Stat. radius (SLR) [mm]	935
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6184
Tread depth (mm)	64,5
Number of lugs	21x2
Tyre capacity 75% [ltr.]	894
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	