

## TYRES

Product group	Tyres
Item number	15726467
Valid tyre size	VF 480 / 80 R 46
LI / SI / PR	177 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Excellent plant and soil protection allows yield increases.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent ride comfort and high machine stability.

## Technical Informations

Item number	15726467
EAN	8903094057306
Valid tyre size	VF 480 / 80 R 46
LI / SI / PR	177 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	222,08
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,60
Section width (mm)	479
Tread width (mm)	450
Outer diameter of tyre [mm].	1936
Stat. radius (SLR) [mm]	889
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5861
Tread depth (mm)	43,5
Number of lugs	30x2
Tyre capacity 75% [ltr.]	439.5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 D	7300	65		3,60	